

TECHNICAL AND MECHANICAL FEATURES				
Feature Description	ES 1.5T S-AWC	LE 1.5T S-AWC	SE 1.5T S-AWC	SEL 1.5T S-AWC
Engine				
Type	1.5L MIVEC DOHC 4-cylinder Direct-Injection Turbocharged			
Engine Code	4B40 TC	4B40 TC	4B40 TC	4B40 TC
Materials	Aluminum block/ aluminum cylinder head			
Bore x Stroke	75.0 mm x 84.8 mm			
Compression Ratio	10.0:1	10.0:1	10.0:1	10.0:1
Displacement	1.5L / 1,499 cc			
Horsepower	152 hp @ 5,500 rpm			
Torque	184 lb.-ft. @ 2,000-3,500 rpm			
Redline RPM	6000	6000	6000	6000
Emissions	TIER 3-BIN 70 (50S) LEV III - ULEV70	TIER 3-BIN 70 (50S) LEV III - ULEV70	TIER 3-BIN 70 (50S) LEV III - ULEV70	TIER 3-BIN 70 (50S) LEV III - ULEV70
Engine Oil Type	0W-20	0W-20	0W-20	0W-20
Recommended Fuel Type	Regular Unleaded	Regular Unleaded	Regular Unleaded	Regular Unleaded
Radiator Core size	687.3x400x27	687.3x400x27	687.3x400x27	687.3x400x27
Transmission				
8-speed CVT with Sport Mode	STD	STD	STD	STD
CVT Automatic Ratios	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378	2.631 - 0.378
1st	2.631	2.631	2.631	2.631
2nd	1.765	1.765	1.765	1.765
3rd	1.313	1.313	1.313	1.313
4th	1.046	1.046	1.046	1.046
5th	0.843	0.843	0.843	0.843
6th	0.664	0.664	0.664	0.664
7th	0.518	0.518	0.518	0.518
8th	0.404	0.404	0.404	0.404
Reverse	1.960	1.960	1.960	1.960
Final Drive	6.386	6.386	6.386	6.386
Suspension				
Front	Macpherson strut with stabilizer bar			
Rear	Multi-link with stabilizer bar			
Steering				
Type	Electric Power Steering	Electric Power Steering	Electric Power Steering	Electric Power Steering
Overall Ratio	14.6	14.6	14.6	14.6
Turns, lock to lock	2.9	2.9	2.9	2.9
Turning circle	34.8 ft	34.8 ft	34.8 ft	34.8 ft
Brakes/ Tires/ Wheels				
Front	Ventilated disc, 11.6 in			
Rear	Solid disc, 11.9 in			
ABS	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD)	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD)	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD)	4-wheel, 4-channel, 4-sensors with Electronic Brake-force Distribution (EBD)
Wheels	16 x 61/2 J Aluminum alloy	18 x 7 J Aluminum alloy	18 x 7 J Aluminum alloy	18 x 7 J Aluminum alloy
Tires	P215/70 R16	P225/55 R18	P225/55 R18	P225/55 R18
Tire Brand	Falken	Bridgestone	Bridgestone	Bridgestone
Temporary Spare Tire	T155/90D16 110M	T155/90D16 110M	T155/80D17 100M	T155/80D17 100M
Exterior Dimensions				
Wheelbase (inches)	105.1	105.1	105.1	105.1
Overall length (inches)	179.0	179.0	179.0	179.0
Overall width (inches)	71.1	71.1	71.1	71.1
Overall height (inches)	66.5	66.5	66.5	66.5
Track, front (inches)	60.6	60.6	60.6	60.6
Track, rear (inches)	60.6	60.6	60.6	60.6
Ground clearance (inches)	8.5	8.5	8.0	8.5
Interior Dimensions				
Head Room (with Panoramic roof)				
Front (inches)	39.5	39.5	39.5 (39.5)	39.5 (39.5)
Rear (inches)	37.3	37.3	37.3 (36.7)	37.3 (36.7)
Leg room				
Front (inches)	40.9	40.9	40.9	40.9
Rear (inches)	35.3	35.3	35.3	35.3
Shoulder room				
Front (inches)	56.2	56.2	56.2	56.2
Rear (inches)	55.1	55.1	55.1	55.1
Hip room				
Front (inches)	53.0	53.0	53.0	53.0
Rear (inches)	52.0	52.0	52.0	52.0
SAE volume				
SAE passenger volume (with Panoramic roof) (cu ft.)	96.7	96.7	96.7 (96.0)	96.7 (96.0)
SAE cargo volume - Behind front seats (with Panoramic roof) (cu ft.)	50.1	50.1	50.1(49.7)	50.1(49.7)
SAE cargo volume - Behind 2nd row seats (with Panoramic roof) (cu ft.)	23.4	23.4	23.4 (23.2)	23.4 (23.2)
Capacities				
Passenger Seating	5	5	5	5
Fuel	15.8 gallons	15.8 gallons	15.8 gallons	15.8 gallons
Oil	4.5 qt	4.5 qt	4.5 qt	4.5 qt
Towing Capacity (lbs.)	1,500	1,500	1,500	1,500
Trailer Tongue Weight (lbs.)	150	150	150	150
Weights				
Curb Weight (lbs.)	3,428	3,472	3,505	3,505
GVWR (lbs.)	4,630	4,630	4,630	4,630
Weight distribution	58/42	58/42	58/42	58/42
Fuel Economy				
City	25	25	25	25
Highway	28	26	26	26
Combined	26	25	25	25
Warranties				
Basic	5-year / 60,000 miles			
Limited Powertrain	10-year / 100,000 miles			
Anti-corrosion	7-year / 100,000 miles			
Roadside Assistance	5 year / Unlimited miles			

Features as of Apr. 1, 2022. Features, packages and additional equipment are based on the latest information available at the time of publication and are subject to change without notice.